

Rockfon® Education Plus

0.80
NRC

Features & Benefits

- Smooth white modern aesthetic
- Economic solution with good sound absorption (NRC = 0.80)
- Fire Performance - Class A
- Lightweight panel, easy to carry and install
- Available in square lay-in and tegular

Applications

- Classroom
- Private office



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Rockfon® Education Plus

LEED® v4.1 Highlights

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓




Recycled Content: 48%





Standard Panels



Packaging Information

Edge Designation	Item Number	Modular Size (nominal)	NRC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton	
 Square Lay-In	SQ	42100	2' x 2' x 3/4"	0.80	A	0.82	up to 100%	-	0.45	80
	SQ	42101	2' x 4' x 3/4"	0.80	A	0.82	up to 100%	-	0.45	80
 Square Tegular Narrow	SLN	42200	2' x 2' x 3/4"	0.80	A	0.82	up to 100%	-	0.57	40
	SLN	42201	2' x 4' x 3/4"	0.80	A	0.82	up to 100%	-	0.57	80
 Square Tegular	SL	42300	2' x 2' x 3/4"	0.80	A	0.82	up to 100%	-	0.57	40
	SL	42301	2' x 4' x 3/4"	0.80	A	0.82	up to 100%	-	0.57	80

Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2'x2' tile, and based on their primary production location.

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4500, 4600 and Fire Rated systems
SQ - Square Lay-In SL - Square Tegular 	SQ - Square Lay-In (2' x 2' & 2' x 4' only) SLN - Square Tegular Narrow 



Rockfon® Education Plus Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 0
 Smoke Developed Index (UL Labeled): 5
 CAN/ULC S102 Flame Spread Index: 5
 Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*
- ✓ Health Product Declaration available*
- ✓ Declare Label available*

* Applicable to all edge types



Cleaning

Vacuum



Environment

48% recycled content



Warranty

30-Year Limited Product Warranty
 See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.6 - 3.1
 RSI Value (Watts Units): 0.46 - 0.54



Hygiene

Stone wool provides no sustenance to microorganisms



Tile Directionality

Rockfon® Education Plus tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°



GREENGUARD Gold Certified
 for Office and Educational
 Environments



CERTIFIED Environmental
 Product Declaration

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
 © ROCKWOOL 2022. All rights reserved.
 ® denotes a trademark that is registered in the United States of America.

060123

Rockfon

4849 S. Austin Ave.
 Chicago, IL 60638 USA

Tel. +1-800-323-7164
 cs@rockfon.com
 rockfon.com