

Rockfon® Medical™ Plus

0.90

NRC

Features & Benefits

- Can be cleaned with diluted solutions of ammonia, chlorine, quaternary ammonium and hydrogen peroxide
- Does not contribute to the growth of MRSA
- Has a low particle emission (ISO Class 4, ISO14644-1) for better air cleanliness
- The rear side of the panel is covered by a back fleece. The edges are sealed.
- Excellent sound absorption (NRC = 0.90)
- Optimal design freedom due to a large selection of edges (lay-in, tegular and concealed)
- Fire Performance - Class A

Applications

- Emergency Room
- Treatment Room
- Patient Room
- Laboratory



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Rockfon® Medical™ Plus

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

Recycled Content: 43%



Standard Panels

Edge Designation	Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton	
	SQ	34100	2' x 2' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.45	80
	SQ	34101	2' x 4' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.45	80
	SLN	34200	2' x 2' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.57	40
	SLN	34201	2' x 4' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.57	80
	SL	34250	2' x 2' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.57	40
	SL	34251	2' x 4' x 3/4"	0.90	-	A	0.83	up to 100%	✓	0.57	80
	CDX	34600	2' x 2' x 7/8"	0.90	-	A	0.83	up to 100%	✓	0.75	40

Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2'x2' tile, and based on their primary production location.

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4200, 4500, 4600 and Fire Rated systems
<p>SQ - Square Lay-In SL - Square Tegular CDX - Fully Concealed</p>	<p>SLN - Square Tegular Narrow</p>



Rockfon® Medical™ Plus Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint and latex laquer on glass scrim surface
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern E



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 0
 Smoke Developed Index (UL Labeled): 5
 CAN/ULC S102 Flame Spread Index: 5
 Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*
- ✓ Health Product Declaration available*
- ✓ Declare Label available*

* Applicable to all edge types



Cleaning

Vacuum
 Damp cloth
 Chemical resistance: resistant to diluted solutions of ammonia, chlorine, quaternary ammonium and hydrogen peroxide



GREENGUARD Gold Certified for Office and Educational Environments



CERTIFIED Environmental Product Declaration



Environment

43% recycled content. Recycled content based on U.S. manufacturing.



Warranty

30-Year Limited Product Warranty
 See rockfon.com



Clean Room

ISO Class 4



Surface Durability

Enhanced durability and dirt resistance



Thermal Insulation

R Value (BTU Units): 2.6 - 3.1
 RSI Value (Watts Units): 0.46 - 0.54



Hygiene

Stone wool provides no sustenance to microorganisms
 Microbiological class M1 fulfilling the requirements of Zone 4 (very high risk) defined by NF S 90-351:2013.

Tested with:

Methicillin Resistant Staphylococcus Aureus (MRSA)
 Candida Albicans

Aspergillus Brasiliensis: The bactericidal and fungicidal effect of dry steam cleaning meets the requirements of NF EN 14561 (> 5 log10) and NF EN 14562 (> 4 log10), meaning the disinfection is very effective.

072022

Rockfon

4849 S. Austin Ave.
 Chicago, IL 60638 USA

2022 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

© ROCKWOOL International A/S 2018. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164

Fax. +1-800-222-3744

rockfon.com