

Rockfon® Color-all™

Design Collection

Features & Benefits

- 34 exclusive colors for acoustic ceilings to inspire and enhance the interior design scheme
- Excellent sound absorption (NRC 0.85 – 0.95)
- Subtle yet playful colors made to mix and match either within the same room or in different areas of a building
- Total design freedom due to exposed, semi-concealed and concealed edges
- Matching grid (main runner, cross tees, perimeter wall angle trim) in an attractive matte finish available

Applications

- Office
- Industry
- Healthcare
- Retail
- Education
- Classroom
- Restaurant
- Reception
- Auditorium



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics



Mold and Mildew Resistance



30-year Warranty Applies to All Stone Wool Tiles and Panels





High Performance Factors

Base Material	Stone Wool
Surface	Smooth Matte Colored Surface
Fire Performance	Class A Tested to US Standard ASTM E84: Flame Spread Index: 5-15 Smoke Developed Index: 0 Canadian Standard CAN/ULC S102: Flame Spread Index: 15 Smoke Developed Index: 5
Warranty	30-Year Tile Warranty

Mold & Mildew Resistance	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
-------------------------------------	---

Sag Resistance	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
-----------------------	---

Low VOC	UL GREENGUARD Gold Certified
----------------	------------------------------



Standard Panels

Edge Designation	Item Number	Modular Size* (nominal)	NRC	Fire Class	Mold & Mildew Resistance	Sag Resistance (relative humidity)	Light Reflectance	Embodied Carbon		Low VOC	Recyclable	lbs/sqft	sqft/carton
								Per 1m ² (kg CO ₂ - eq)	Per 1ft ² (kg CO ₂ - eq)				
 Square Lay-In	11100	2' x 2' x 5/8"	0.90	A	✓	up to 100%	Color Dependant	3.36	0.312	✓	✓	0.47	112
	11101	2' x 4' x 5/8"	0.90	A	✓	up to 100%	Color Dependant	3.36	0.312	✓	✓	0.47	112
 Square Tegular	11250	2' x 2' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	✓	0.69	40
	11251	2' x 4' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	✓	0.69	80
 Square Tegular Narrow	11200	2' x 2' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	✓	0.69	40
	11201	2' x 4' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	✓	0.69	80
 Fully Concealed	11600	2' x 2' x 7/8"	0.95	A	✓	up to 100%	Color Dependant	3.75	0.350	✓	✓	0.75	40
	11601	2' x 4' x 7/8"	0.95	A	✓	up to 100%	Color Dependant	3.75	0.350	✓	✓	0.75	80

* Refer to the Rockfon® Module System brochure for module tile sizes.

Product Compatibility

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4200, 4500 and Fire Rated systems
 SQ Square Lay-in SL Square Tegular CDX Fully Concealed	 SQ' - Square Lay-in (2' x 2' & 2' x 4' only) SLN - Square Tegular Narrow 4000 - Tempra 4000 - Tempra 4200 - Integrity 4500 - Ultraline 1/4" reveal

Mustard - 751	Sand - 730	Stucco - 720			
Light reflectance: 0.36	Light reflectance: 0.55	Light reflectance: 0.70			
Scarlet - 771	Coral - 776	Seashell - 775	Petal - 774		
Light reflectance: 0.08	Light reflectance: 0.21	Light reflectance: 0.55	Light reflectance: 0.70		
Seaweed - 734	Eucalyptus - 732	Sage - 731	Mint - 712		
Light reflectance: 0.05	Light reflectance: 0.12	Light reflectance: 0.34	Light reflectance: 0.70		
Space - 749	Storm - 748	Azure - 747	Fresh - 742		
Light reflectance: 0.04	Light reflectance: 0.08	Light reflectance: 0.34	Light reflectance: 0.51		
Earth - 725	Clay - 726	Linen - 722	Sandalwood - 713	Chalk - 721	
Light reflectance: 0.22	Light reflectance: 0.22	Light reflectance: 0.29	Light reflectance: 0.49	Light reflectance: 0.51	
Ebony - 728	Cork - 724	Hemp - 723			
Light reflectance: 0.04	Light reflectance: 0.30	Light reflectance: 0.45			
Iron - 718	Concrete - 706	Mastic - 704	Zinc - 705	Mercury - 762	
Light reflectance: 0.07	Light reflectance: 0.16	Light reflectance: 0.33	Light reflectance: 0.33	Light reflectance: 0.44	
Charcoal - 709	Anthracite - 708	Gravel - 703	Plaster - 702	Stone - 701	Moon - 710
Light reflectance: 0.04	Light reflectance: 0.07	Light reflectance: 0.34	Light reflectance: 0.58	Light reflectance: 0.55	Light reflectance: 0.74

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool.
Samples of the colored surfaces are available upon request.

Rockfon® Color-all™ Service Level Guide

Tier 1

Colors	Availability	Sizes	Edge Types
Charcoal - 709 Concrete - 706 Hemp - 723 Stone - 701	Tile and matching grid available in 1 week (if <3,000 SF)	2x2	SQ, SL, SLN, CDX

✓ Great for fast turnaround and smaller projects.

Tier 2

Colors	Availability	Sizes	Edge Types
Fresh - 742 Azure - 747 Storm - 748 Anthracite - 708 Stucco - 720 Mastic - 704 Linen - 722 Sage - 731	Tile and matching grid available in 6 weeks (if <1,500 SF)	2x2	SQ, SLN

Charcoal - 709	Tile and matching grid available in 6 weeks (if <1,500 SF)	2x4	SQ
--------------------------------------	--	-----	----

✓ Use when more design variety is needed, but still manageable lead time.

Tier 3

Colors	Availability	Sizes	Edge Types
751 Mustard 730 Sand 720 Stucco 775 Seashell 774 Petal 713 Sandalwood 721 Chalk 771 Scarlet 776 Coral 725 Earth 726 Clay 722 Linen 724 Cork 723 Hemp 734 Seaweed 732 Eucalyptus 731 Sage 712 Mint 742 Fresh 747 Azure 762 Mercury 749 Space 748 Storm 718 Iron 706 Concrete 704 Mastic 705 Zinc 703 Gravel 728 Ebony 709 Charcoal 708 Anthracite 702 Plaster 701 Stone 710 Moon	Tile and matching grid available in 16 weeks	2x2, 2x4, Custom Sizes	SQ, SL, SLN, CDX ■ All Made-to-Order Color-All Square Edge (SQ) tiles = 300 sqft minimum ■ For all other sizes and edge types (SL, SLN, CDX), a minimum of 6,000 sqft per color applies. Different edge types (SL, SLN, CDX) and sizes may be combined within the same color, provided each variation is at least 1,000 sqft ■ For additional details or to confirm availability, please contact Rockfon Customer Service

✓ Perfect for large-scale or design-driven projects that require full line flexibility.

Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		250348	935.00	Universal Hold Down Clip	1000	16
		252923	425.01	Hold Down Clip for 5/8" Board 250/1250 Systems	200	2
		250343	820.00	Hold Down Clip for 5/8" Board 250/1250 Systems	1000	7
		237949	490.00	Hold Down Clip for 0" - 3/4" Panels (Black)	100	2
		237952	491.00	Hold Down Clip for 3/4" - 1-1/4" Panels (Blue)	150	2
		237954	492.00	Hold Down Clip for 1-1/2" Panels (Grey)	100	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15
		250325	427.01	Butterfly Retention Clip for 1" - 2" Panels	150	15

*Clips should be chosen as per tile thickness

[Scan for Full
Accessories Guide](#)



Rockfon® Color-all™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with pre-painted glass scrim surface.



ASTM E1264 Classification

ASTM E1264 (2022) : Type IV, Form 3, Pattern G
ASTM E1264 (2023): Type A, Form A2.3, Pattern G



Fire Performance

Rockfon® Color-all™ tiles are tested for Surface Burning Characteristics to UL 723 (ASTM E84) for the US and CAN/ULC-S102 for Canada, and achieve:

Tested to US Standard Flame Spread Index: 5-15
UL 723 (ASTM E84): Smoke Developed Index: 0

Canadian Standard Flame Spread Index: 15
CAN/ULC S102: Smoke Developed Index: 5



Mold and Mildew Resistance

Stone wool is inherently resistant to mold and mildew without added antimicrobials. Both, tile surface and substrate, are tested to:

- ✓ ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings)
- ✓ ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings)



Humidity Resistance

Stone wool ceiling tiles are inherently humidity resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity



Cleaning

- ✓ Vacuum



Thermal Resistance

R 3.47 hr.ft².°F/Btu per 1 inch (I-P)
R 0.61 m².K/W per 25.4 mm (SI)



Tile Directionality

Rockfon Color-all® tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°; not 90°



Warranty

30-Year Limited Product Warranty.
See rockfon.com

Sustainability



Transparency

- ✓ Environmental Product Declaration (Product-Specific, Type III)
- ✓ Cradle to Cradle Certified
Applicable to all edge types



Low-Emitting Materials

UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3 for SQ Edge: 3.36 kg CO₂-eq (per 1m²) / 0.312 kg CO₂-eq (per 1ft²)

For all other edge types, refer to p. 2



Rockcycle - Closed Loop Recycle Program

All stone wool ceiling tiles are eligible for the Rockcycle program. Please contact rockcycle@rockfon.com for more information



Discover Rockfon® Color-all™

on Ecomedes and see how it aligns with the Common Materials Framework (CMF).

Find us on

MasterSpec®
Powered by Delttek Specpoint®

BIM/Revit objects available at:
rockfon.com/products/rockfon-color-all/