

Rockfon® Education Premium


0.90 NRC

Features & Benefits

- Smooth white modern aesthetic
- Economic solution with good sound absorption (NRC = 0.90)
- Fire Performance Class A
- Lightweight panel, easy to carry and install
- Available in square lay-in and tegular

Applications

- Library
- Media center



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Rockfon® Education Premium

LEED® v4.1 Highlights

Materials and Resources (MR)

Sourcing of Raw Materials Material Ingredients

Indoor Environmental Quality (EQ)














Packaging Information

Edge Designation		Item Number	Modular Size (nominal)	NRC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/ sqft	sqft/ carton
Square Lay-In	SQ	43100	2' x 2' x 1"	0.90	А	0.84	up to 100%	✓	0.69	64
	SQ	43101	2' x 4' x 1"	0.90	А	0.84	up to 100%	✓	0.69	64
Square Tegular Narrow	SLN	43200	2' x 2' x 1"	0.90	А	0.84	up to 100%	✓	0.69	32
	SLN	43201	2' x 4' x 1"	0.90	А	0.84	up to 100%	✓	0.69	64
Square Tegular	SL	43300	2' x 2' x 1"	0.90	А	0.84	up to 100%	✓	0.69	32
	SL	43301	2' x 4' x 1"	0.90	А	0.84	up to 100%	✓	0.69	64

Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2'x2' tile, and based on their primary production location.





Rockfon® Education Premium Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index (UL Labeled): 5 CAN/ULC S102 Flame Spread Index: 5 Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*
- ✓ Health Product Declaration available*
- ✓ Declare Label available*
 - * Applicable to all edge types



Cleaning

Vacuum



Environment

49% recycled content



Warranty

30-Year Limited Product Warranty See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.6 - 3.5 RSI Value (Watts Units): 0.46 - 0.62



Hygiene

Stone wool provides no sustenance to microorganisms



Tile Directionality

Rockfon® Education Premium tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°.



GREENGUARD Gold Certified for Office and Educational Environments



CERTIFIED Environmental Product Declaration

060123

Rockfon

4849 S. Austin Ave. Chicago, IL 60638 USA

Tel. +1-800-323-7164 cs@rockfon.com rockfon.com

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

ROCKWOOL A/S 2022. All rights reserved.

[®] denotes a trademark that is registered in the United States of America.