

# Rockfon® Color-all™ Standard Program

**UP TO  
0.95  
NRC**

## Features & Benefits

- Charcoal, Concrete, Stone and Hemp available at faster "B" service level for the standard tile & grid sizes in smaller quantities
- Optimal design freedom due to the variety of colors and edges types (SQ, SL, SLN, CDX)
- Color-all grid now with has a smooth matte finish
- Excellent sound absorption (NRC= 0.85- 0.95)
- Fire Performance - Class A

## Applications

- Office
- Industry
- Healthcare
- Retail
- Classroom
- Restaurant
- Reception
- Auditorium



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic Absorption**



**Fire Performance - Class A**



**Moisture and Sag Resistance**




**Smooth, Modern Aesthetics**

# Rockfon® Color-all™ Standard Program

Square Lay-in (SQ), Square Tegular (SL), Square Tegular Narrow (SLN), and Fully Concealed (CDX) panels and below suspension systems are available as "B" stock items in the following Color-All™ colors:

## Updated Tile and Grid Color Offerings

### All Smooth Matte Finish


	Color Name
	701 Stone
	706 Concrete
	723 Hemp
	709 Charcoal

## Grid Selection with Updated Color Offering

Part Description	Part Number		Feet/Carton
	Suspension System		
	1200 15/16"	4000 9/16"	
Main Runner	211.XXX (ID) 200.XXX.XXX (HD)	4000.XXX	240
2' Cross Tee	1202.XXX	4022.XXX	120
4' Cross Tee	1210.XX	4014.XXX	240
Wall Angle	21420.XXX	1480.XXX	300

Last digits in part numbers correspond to tile color number.

## Tile Selection with Updated Color Offering

Edge Designation	Part Number	Modular Size*	Square Feet/Carton
Square Lay-in 	11100	2' x 2' x 5/8"	112
Square Tegular 	11250	2' x 2' x 3/4"	40
Square Tegular Narrow 	11200	2' x 2' x 3/4"	40
Fully Concealed 	11600	2' x 2' x 7/8"	40

\*Refer to the Rockfon® Module System brochure for module tile sizes.





## Rockfon® Color-all™ Standard Program Properties

### Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface  
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



#### Fire Performance

Surface burning characteristics:  
 UL723 (ASTM E84) Flame Spread Index: 5-15  
 Smoke Developed Index (UL Labeled): 0  
 CAN/ULC S102: Flame Spread Index: 15  
 Smoke Developed Index: 0  
*Flame Spread Index is color dependant*



#### Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available\*
- ✓ Environmental Product Declaration available\*

\* Applicable to all edge types



#### Cleaning

Vacuum



#### Environment

41% recycled content. Recycled content based on European manufacturing.



#### Warranty

30-Year Limited Product Warranty  
 See rockfon.com



#### Thermal Insulation

R Value (BTU Units): 2.2 - 3.1  
 RSI Value (Watts Units): 0.39 - 0.54



#### Hygiene

Stone wool provides no sustenance to microorganisms



GREENGUARD Gold Certified  
 for Office and Educational  
 Environments



CERTIFIED Environmental  
 Product Declaration

2022 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.  
 © ROCKWOOL A/S 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

072922

**Rockfon**

4849 S. Austin Ave.  
 Chicago, IL 60638 USA

Tel. +1-800-323-7164

cs@rockfon.com

rockfon.com