

Rockfon[®] Education Premium Rockfon

Final Assembly: Marshall County, Mississippi, USA

Life Expectancy: 50 Year(s)

Embodied Carbon: 1.32 kg CO2-Eq Declared Unit: 1 m2 of installed ceiling tile

End of Life Options: Recyclable (90%), Landfill (10%)

Ingredients:

Stone wool, biosoluble; Aluminum hydroxide; Fiberglass; Syrups, hydrolyzed starch; Phenol, polymer with formaldehyde¹; Water; Limestone; Urea; Polyvinyl alcohol; Undisclosed (< 0.5%)²; Caprolactam; Laurolactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Urea, polymer with formaldehyde¹; Residual oils (petroleum), solvent-dewaxed; Titanium dioxide; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²

¹LBC Temp Exception RL-009 - Formaldehyde ²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

■ LBC Red List Approved VO

Declared

% Disclosed: 99.3% at 100ppm VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0016 EXP. 01 JAN 2026

Original Issue Date: 2021