

1. Identification

Product identifier	Rockfon Acoustical Ceiling Tiles and Wall Panels
Other means of identification	
Synonyms	Alaska, Artic, Cinema Black, Contour Baffles, Education Plus, Education Premium, Education Standard, Facett, Hygienic Plus, Impact, Industrial, Island, Korral, Medical Air, Medical Plus, Medical Standard, Multiflex Baffle, Pacific, Sonar, Sonar Activity, Tropic, Winter.
Recommended use	Suspended ceilings for use internally in buildings.
Recommended restrictions	Use in accordance with manufacturer's recommendations.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer/Supplier	Roxul USA Inc., d.b.a. Rockfon 4849 S. Austin Ave. Chicago, IL 60638 USA
Telephone:	+1-800-323-7164
Contact:	techservices@rockfon.com
Emergency Phone Number:	3E Global Incident Response Hotline USA/Canada +1.866.519.4752 Access Code: 337140

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.

As supplied, the product is expected to pose no immediate health or fire hazard. Dusts generated during subsequent processing may pose the hazards described in this Safety Data Sheet.

Label elements

Hazard symbol	None.
Signal word	None.
Hazard statement	None.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Get medical attention/advice if you feel unwell.
Storage	Store as indicated in Section 7.
Disposal	Dispose of in accordance with local, state, and federal regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Stone wool, biosoluble	65997-17-3	50 - 99
Aluminum hydroxide	21645-51-2	< 6
Limestone	1317-65-3	< 6
Calcium carbonate, synthetic	471-34-1	< 5
Kaolin	1332-58-7	≤ 5
Titanium dioxide	13463-67-7	≤ 5

Chemical name	CAS number	%
epsilon-Caprolactam	105-60-2	< 2
Adipic acid	124-04-9	≤ 1
Citric Acid	77-92-9	≤ 1
Hexamethylenediamine	124-09-4	< 1
Lauro lactam	947-04-6	≤ 1
Talc	14807-96-6	≤ 1
Urea	57-13-6	≤ 1
Butyl acrylate	141-32-2	< 0.1
Styrene	100-42-5	< 0.1

Composition comments

All concentrations are in percent by weight.
 Components not listed are either non-hazardous or are below reportable limits.
 The manufacturer has claimed the specific chemical identity and/or exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Under normal conditions of intended use, this product is not expected to be a health risk. Dust may irritate the respiratory system.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry chemical powder. Carbon dioxide (CO2). Sand.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe dust. Provide adequate ventilation. Ventilate the area. See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Minimize dust generation and accumulation. Wet down with water and dike for later disposal. Shovel the material into waste container. Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Use work methods which minimize dust production. Avoid inhalation of dust and contact with skin and eyes. Ensure adequate ventilation. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Please see manufacturer guidelines for safe storage. Keep in original container. The products must be stacked flat on level floor with protective panels or sheets between products and floor. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-2 Permissible Exposure Limits (PEL) (29 CFR 1910.1000)

Components	Type	Value
Styrene (CAS 100-42-5)	Ceiling	200 ppm
	TWA	100 ppm

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Limestone (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	0.1 mg/m ³	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Adipic acid (CAS 124-04-9)	TWA	5 mg/m ³	
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m ³	Respirable fraction.
epsilon-Caprolactam (CAS 105-60-2)	TWA	5 mg/m ³	Inhalable fraction and vapor.
Hexamethylenediamine (CAS 124-09-4)	TWA	0.5 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable fraction.
Styrene (CAS 100-42-5)	STEL	20 ppm	
	TWA	10 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m ³	Respirable finescale particles

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Styrene (CAS 100-42-5)	IDLH	0.9 % 700 ppm
Talc (CAS 14807-96-6)	IDLH	1000 mg/m3
Titanium dioxide (CAS 13463-67-7)	IDLH	5000 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
epsilon-Caprolactam (CAS 105-60-2)	STEL	3 mg/m3	Vapor.
		3 mg/m3	Dust.
		0.66 ppm	Vapor.
	TWA	1 mg/m3	Dust.
		1 mg/m3	Vapor.
		0.22 ppm	Vapor.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Styrene (CAS 100-42-5)	STEL	425 mg/m3	
		100 ppm	
	TWA	215 mg/m3	
Talc (CAS 14807-96-6)	TWA	50 ppm	
		2 mg/m3	Respirable.

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value	Form
Hexamethylenediamine (CAS 124-09-4)	TWA	5 mg/m3	
Urea (CAS 57-13-6)	TWA	1 ppm	
		10 mg/m3	Total particulate.

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Styrene (CAS 100-42-5)	150 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*
	40 ug/l	Styrene	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Styrene (CAS 100-42-5) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Styrene (CAS 100-42-5) Skin designation applies.

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Contact with dust: Wear approved safety goggles.
Skin protection	
Hand protection	Contact with dust: Wear protective gloves.
Other	Wear suitable protective clothing.
Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid.
Color	Various colors.
Odor	Low to no odor.
Odor threshold	Not applicable.
pH	Material is non soluble in water.
Melting point/freezing point	> 1832 °F (> 1000 °C)
Initial boiling point and boiling range	Property has not been measured.
Flash point	Not applicable, material is a solid.
Evaporation rate	Not applicable, material is a solid.
Flammability (solid, gas)	Non flammable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.
Vapor pressure	Property has not been measured.
Vapor density	Not applicable, material is a solid.
Relative density	Property has not been measured.
Solubility(ies)	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
Viscosity	Not applicable, material is a solid.
Other information	
Density	70 - 165 kg/m ³
Kinematic viscosity	Not applicable, material is a solid.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids.
Hazardous decomposition products	Fumes. Carbon oxides. When stone wool is heated above approximately 200°C (392°F), binder components and decomposition gases are emitted from the binder which can be detected by odour.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Under normal conditions of intended use, this material does not pose a risk to health. Dusts may irritate the respiratory tract.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Aluminum hydroxide (CAS 21645-51-2)		
Acute		
Oral		
LD50	Rat	> 5000 mg/kg
Calcium carbonate, synthetic (CAS 471-34-1)		
Acute		
Oral		
LD50	Rat	6450 mg/kg
epsilon-Caprolactam (CAS 105-60-2)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	1475 mg/kg
Kaolin (CAS 1332-58-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
Lauro lactam (CAS 947-04-6)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	2330 mg/kg (OECD 401)
Talc (CAS 14807-96-6)		
Acute		
Dermal		
LD50	Rat	20000 mg/kg

Components	Species	Test Results
Inhalation		
LC50	Rat	2.1 mg/l, 4 hours
Oral		
LD50	Rat	3870 - 5000 mg/kg
Titanium dioxide (CAS 13463-67-7)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 6.82 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Urea (CAS 57-13-6)		
<u>Acute</u>		
Oral		
LD50	Mouse	11500 - 13000 mg/kg
	Rat	14300 - 15000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Due to the form of the product, exposure to the potentially carcinogenic components is not expected.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
epsilon-Caprolactam (CAS 105-60-2)	3 Not classifiable as to carcinogenicity to humans.	
Stone wool, biosoluble (CAS 65997-17-3)	3 Not classifiable as to carcinogenicity to humans.	
Styrene (CAS 100-42-5)	2A Probably carcinogenic to humans.	
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
NTP Report on Carcinogens		
Styrene (CAS 100-42-5)	Reasonably Anticipated to be a Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	No other specific acute or chronic health impact noted.	

12. Ecological information

Ecotoxicity Not relevant, due to the form of the product.

Components	Species	Test Results
Calcium carbonate, synthetic (CAS 471-34-1)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) > 56000 mg/l, 96 Hours
epsilon-Caprolactam (CAS 105-60-2)		
Fish	LC50	Salmo gairdneri 707.1 mg/l, 96 hours

Components		Species	Test Results
Aquatic			
Algae	EC50	Selenastrum capricornutum	> 1000 mg/l, 72 hours
Crustacea	EC50	Daphnia magna	> 1000 mg/l, 48 hours
Fish	LC0	Oryzias latipes	100 mg/l, 96 hours
Other			
Bacteria	EC50	Pseudomonas putida	4240 mg/l, 17 hours
Hexamethylenediamine (CAS 124-09-4)			
Aquatic			
Algae	NOEC	Pseudokirchneriella subcapitata	10 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna	50 mg/l, 48 Hours
	NOEC	Daphnia	4.2 mg/l, 21 days
Fish	LC50	Pimephales promelas	1825 mg/l, 96 Hours pH adjusted
Kaolin (CAS 1332-58-7)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia magna	> 1.1 g/l, 48 Hours
Lauro lactam (CAS 947-04-6)			
Aquatic			
<i>Acute</i>			
Algae	ErC50	Desmodesmus subspicatus	172 mg/l, 72 hours (OECD 201)
Crustacea	EC50	Daphnia magna	59 mg/l, 48 hours (OECD 202)
Fish	LC50	Cyprinus carpio	63 mg/l, 96 hours (OECD 203)
Talc (CAS 14807-96-6)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	7203 mg/l, 96 hours
Crustacea	LC50	Aquatic Invertebrates	36812 mg/l, 48 hours
Fish	LC50	Fish	> 895810 - < 1100000 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Pseudokirchneriella subcapitata	> 100 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna	> 100 mg/l, 48 hours
Fish	LC50	Oncorhynchus mykiss	> 100 mg/l, 96 hours
Urea (CAS 57-13-6)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Aquatic Invertebrates	10000 mg/l, 24 hours
Fish	LC50	Fish	18100 mg/l, 24 hours
			12100 mg/l, 72 hours
			> 10000 - < 1786 mg/l, 48 hours
			> 6810 - < 22500 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Adipic acid (CAS 124-04-9)	0.08
Lauro lactam (CAS 947-04-6)	2.71
Styrene (CAS 100-42-5)	2.95
Urea (CAS 57-13-6)	-2.11
epsilon-Caprolactam (CAS 105-60-2)	0.12

Mobility in soil The product is insoluble in water.
Other adverse effects This product contains one or more substances identified as hazardous air pollutants (HAPs) per the US Federal Clean Air Act (see section 15).

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations Dispose in accordance with all applicable regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Adipic acid (CAS 124-04-9) Listed
Styrene (CAS 100-42-5) Listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Styrene	100-42-5	< 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Styrene (CAS 100-42-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Styrene (CAS 100-42-5) Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

Adipic acid (CAS 124-04-9)
Calcium carbonate, synthetic (CAS 471-34-1)
epsilon-Caprolactam (CAS 105-60-2)
Hexamethylenediamine (CAS 124-09-4)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Styrene (CAS 100-42-5)
Talc (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Adipic acid (CAS 124-04-9)
Calcium carbonate, synthetic (CAS 471-34-1)
epsilon-Caprolactam (CAS 105-60-2)
Hexamethylenediamine (CAS 124-09-4)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Stone wool, biosoluble (CAS 65997-17-3)
Styrene (CAS 100-42-5)
Talc (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Adipic acid (CAS 124-04-9)
Calcium carbonate, synthetic (CAS 471-34-1)
epsilon-Caprolactam (CAS 105-60-2)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Styrene (CAS 100-42-5)
Talc (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Adipic acid (CAS 124-04-9)
Calcium carbonate, synthetic (CAS 471-34-1)
epsilon-Caprolactam (CAS 105-60-2)
Limestone (CAS 1317-65-3)
Stone wool, biosoluble (CAS 65997-17-3)
Styrene (CAS 100-42-5)
Talc (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Styrene (CAS 100-42-5)	Listed: April 22, 2016
Talc (CAS 14807-96-6)	Listed: April 1, 1990
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 20-November-2024

Revision date -

Version # 01

NFPA ratings



Disclaimer

Roxul USA Inc., d.b.a. Rockfon cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.