

Rockfon® Impact™


0.85
NRC

Features & Benefits

- A reinforced glass scrim enhancing impact resistance
- Good sound absorption (NRC = 0.85)
- Fire Performance - Class A
- High light reflectance (LR = 0.86)
- Available in square lay-in

Applications

- Recreational Center
- Convention Center



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

Recycled Content: up to 27%



Standard Panels

Edge Designation	Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton	
	SQ	4100	2' x 2' x 3/4"	0.85	-	A	0.86	up to 100%	✓	0.45	80
	SQ	4200	2' x 2' x 1 1/2"	0.85	-	A	0.86	up to 100%	✓	0.82	40

15/16" Suspension Systems

200, 1200 and Fire Rated systems

SQ - Square Lay-In





Rockfon® Impact™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on reinforced glass scrim to increase impact resistance
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern E



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 0
 Smoke Developed Index (UL Labeled): 5
 CAN/ULC S102 Flame Spread Index: 5
 Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen



Cleaning

Vacuum
 Damp cloth



Environment

Up to 27% recycled content. Recycled content based on European manufacturing.



Warranty

30-Year Limited Product Warranty
 See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.6 - 5.3
 RSI Value (Watts Units): 0.46 - 0.92



Hygiene

Stone wool provides no sustenance to microorganisms



Impact Resistance

Rockfon Impact's capability to withstand incidental or occasional ball impact has been tested. For more details, please contact customer service.



Tile Directionality

Rockfon Impact™ tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°.



GREENGUARD Gold Certified
 for Office and Educational
 Environments

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
 © ROCKWOO 2022. All rights reserved.
 ® denotes a trademark that is registered in the United States of America.

060123

Rockfon

4849 S. Austin Ave.
 Chicago, IL 60638 USA

Tel. +1-800-323-7164
 cs@rockfon.com
 rockfon.com